



# T Series

## Half-Door Refrigerators

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*		
<b>SOLID HALF DOORS</b>									
T-23-2	2 s/s	23	3	1/3	7.5	275	27 x 29 1/2 x 78 3/8		
T-49-4	4 s/s	49	6	1/2	9.5	430	54 1/8 x 29 1/2 x 78 3/8		
T-72-6	6 s/s	72	9	1/2	11.8	615	78 1/8 x 29 1/2 x 79 1/8		
<b>GLASS HALF DOORS</b>									
T-23G-2	2 g/s	23	3	1/3	7.9	300	27 x 29 3/4 x 78 3/8		
T-49G-4	4 g/s	49	6	1/2	10.0	490	54 1/8 x 29 3/4 x 78 3/8		
T-72G-6	6 g/s	72	9	1/2	12.9	700	78 1/8 x 29 3/4 x 79 1/8		
<b>COMBINATION HALF DOORS</b>									
T-23-1-G-1	1 g/s - 1 s/s	23	3	1/3	8.0	285	27 x 29 3/4 x 78 3/8		
T-49-2-G-2	2 g/s - 2 s/s	49	6	1/2	10.0	460	54 1/8 x 29 3/4 x 78 3/8		
T-72-3-G-3	3 g/s - 3 s/s	72	9	1/2	12.9	650	78 1/8 x 29 3/4 x 79 1/8		

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1 3/8" for door handle (glass door models only).

\* Height does not include 5" for castors or 6" for optional legs.

## Pass-Thru Refrigerator

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions L D H*		
<b>SOLID HALF DOORS</b>									
T-49-4-PT	6 s/s	49	6	1/2	9.5	535	54 1/8 x 32 1/8 x 78 3/8		

All dimensions rounded up to the nearest 1/8".

\* Height does not include 5" for castors or 6" for optional legs.



T-23-2



T-72G-6



T-49-2-G-2

### FEATURES/BENEFITS

- **Oversized and balanced, (134A), refrigeration system**, factory sealed and pre-lubricated for long life - holds **33°F to 38°F**.
- **300 series stainless steel front** (the finest stainless available).
- Interior - attractive, **NSF approved**, white aluminum and **300 series stainless floor**.
- Anodized quality aluminum ends, back and top.
- Positive seal self-closing doors with factory tested (over 1,000,000 times) **lifetime guaranteed door hinges and torsion type closure system**.
- Extruded, aluminum door frames on glass doors.
- Adjustable, **heavy duty, PVC coated wire shelves**.
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- **4" diameter swivel castors standard** equipment.
- **Door locks standard**.
- Exterior mounted temperature monitor.
- Legs available for all models.
- **Energy efficient, "Low-E", thermal glass doors** (glass door models).
- **Fluorescent interior lighting**; patented integrated door light (IDL) standard on glass & combination door models.
- Incandescent interior lighting on solid door models.
- **Lifetime guaranteed recessed door handles** standard on solid half doors.

- **Bottom Mounted Units Have...**
- A "no-stoop", lower shelf.
- Allows for top storage.
- Compressor performs in the coolest, most grease-free area of kitchen for ease of compressor load.
- Compressor can be serviced easily, and accessed by a single repairman.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.