



T Series

Glass Door -10°F Freezers

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H*
T-12FG	1	12	3	1/2	9.0	290	24 ⁷ / ₈	23 ³ / ₈	63 ¹ / ₈
T-23FG	1	23	3	3/4	13.0	405	27	29 ³ / ₄	78 ³ / ₈
T-49FG ‡	2	49	6	1 1/2	12.3	600	54 ¹ / ₈	29 ³ / ₄	78 ³ / ₈
NEW T-72FG ‡	3	72	9	1 1/2	14.1	N/A	78 ¹ / ₈	29 ³ / ₄	79 ¹ / ₈

All dimensions rounded up to the nearest 1/8".

- † Depth does not include 1³/₈" for door handles.
- * Height does not include 5" for castors or 6" for optional legs.
- T-12FG standard with leg levelers, optional 2¹/₂" diameter castors available, legs not available.
- * Height on T-12FG does not include 1" for upper hinge bracket.
- ‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



T-12FG

Solid Half Door -10°F Freezers

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D	H*
T-23F-2	2 s/s	23	3	1/2	10.4	300	27	29 ¹ / ₂	78 ³ / ₈
T-49F-4	4 s/s	49	6	3/4	13.2	530	54 ¹ / ₈	29 ¹ / ₂	78 ³ / ₈

All dimensions rounded up to the nearest 1/8".

- * Height does not include 5" for castors or 6" for optional legs.



T-49FG

True
freezers
hold
-10°F



T-23F-2

FEATURES/BENEFITS

- **Oversized and balanced, environmentally friendly (R404A), refrigeration system.**
- **-10°F temperature** (air off evaporator coil, -20°F) holds frozen food and ice cream.
- **300 series stainless steel front** (the finest stainless available).
- Interior - attractive, **NSF approved**, white aluminum and **300 series stainless floor.**
- Anodized quality aluminum ends, back and top.
- Large evaporator and coil heater permit short defrost cycle.
- Adjustable, **heavy duty, PVC coated wire shelves.**
- Automatic defrost system time-initiated, temperature-terminated.
- Recessed handles standard on solid half-doors.
- **Energy efficient, triple pane, thermal insulated glass on glass door models.**
- Incandescent interior lighting on solid door models.
- Fluorescent interior lighting; integrated door light (IDL) standard on glass door models (excludes T-12FG).
- Positive seal self-closing doors with factory tested (over 1,000,000 times) **lifetime guaranteed door hinges and torsion type closure system.**
- Extruded, aluminum door frames on glass doors.
- **Lifetime guaranteed recessed door handles** on solid doors.
- **Standard backguard** improves airflow.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Exterior mounted temperature monitor. (not available on T-12FG)
- **4" diameter swivel castors** standard equipment (leg levelers standard for T-12FG, 2¹/₂" castors optional). 6" legs available for all models except T-12FG.
- Door locks standard (not available on T-12FG).

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.