

Reach-In Dual Temperature

Model	Swing Doors	Cu. Ft.		HP ref. - frzr	Amps	Crated Weight	Cabinet Dimensions		
		ref. - frzr					L	D†	H*
SOLID DOORS									
TA1DT-2HS	2	13	13	1/5 - 1/3	13.2	430	29	x 34 ³ / ₄	x 78 ¹ / ₄
TA2DT-2S ‡	2	26	24	1/3 - 1/2	12.2	725	51 ³ / ₈	x 34 ³ / ₄	x 78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for rear freezer condensate enclosure.

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components on TA2DT-2S.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



TA2DT-2S



TA1DT-2HS

FEATURES/BENEFITS

- True's dual temperature models are equipped with **two, self-contained, independent refrigeration systems** (CFC free).
- Refrigerator holds 33°F to 38°F. Freezer holds -10°F.
- TA1DT-2HS features refrigerator on top and freezer on bottom.
- TA2DT-2S features refrigerator on left and freezer on right.
- Compartmentalized, incandescent, interior lighting (one for each door).
- **Shelving** - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. (field installation required).
- Exterior - **300 series stainless steel front, sides, bottom and back** (the finest stainless available).
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner**.
- Automatic evaporator fan motor delay during defrost cycle.
- Minimum wattage heater in cabinet frame and door.
- Dual exterior mounted temperature monitors.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- Freezer compartment **standard with back-guard** to improve airflow.
- Automatic defrost system time-initiated, time-terminated in single section models; time-initiated, temperature-terminated in two section models.
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges**.
- **Lifetime guaranteed recessed door handles**.
- Door locks standard.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.