

## Reach-In Freezers



TA1F-1G

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
<b>SOLID DOORS</b>						
TA1F-1S	1 s/s	31	1/2	108	410	29 x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA2F-2S	2 s/s	56	3/4	13.0	704	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA3F-3S ‡	3 s/s	85	1 1/2	11.8	790	76 <sup>1</sup> / <sub>2</sub> x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>SOLID HALF DOORS</b>						
TA1F-2HS	2 s/s	31	1/2	108	410	29 x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA2F-4HS	4 s/s	56	3/4	13.0	704	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA3F-6HS ‡	6 s/s	85	1 1/2	11.8	790	76 <sup>1</sup> / <sub>2</sub> x 34 <sup>3</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>GLASS DOORS</b>						
<b>NEW</b> TA1F-1G	1 g/s	31	3/4	10.2	435	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>NEW</b> TA2F-2G ‡	2 g/s	56	1	9.1	N/A	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>

All dimensions rounded up to the nearest 1/8"

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handles (glass door models only).

\* Height does not include 5" for castor height or 6" for optional legs.

\* Height does not include 1" for system mechanical components.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.

## Pass-Thru Freezer



TA2FPT-2S-2S

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*
<b>SOLID DOORS</b>						
TA2FPT-2S-2S ‡	4 s/s	56	1	9.1	754	51 <sup>3</sup> / <sub>8</sub> x 37 <sup>1</sup> / <sub>4</sub> x 78 <sup>1</sup> / <sub>4</sub>

All dimensions rounded up to the nearest 1/8"

\* Height does not include 5" for castor height or 6" for optional legs.

\* Height does not include 1" for system mechanical components.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



TA3F-3S

## FEATURES/BENEFITS

- **Environmentally friendly (R404A), refrigerant.**
- **Freezer holds -10°F** (air off evaporator coil, -20°F) for the best in food preservation.
- **Shelving** - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. (field installation required).
- Exterior - **300 series stainless steel front, sides, bottom and back** (the finest stainless available).
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and solid door liner.**
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.

- Minimum wattage heater in cabinet frame and door.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- **Lifetime guaranteed recessed door handles on solid doors.**
- Door locks standard.
- Exterior mounted **digital electronic thermometer** features manual defogger.
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges.**
- **Standard backguard** improves airflow (excludes pass-thru model).
- **4" diameter swivel castors** standard equipment. 6" legs available.

- Incandescent interior lighting on solid door models; Fluorescent interior lighting, integrated door light (IDL) on glass door models.
- Energy efficient, triple pane, thermal insulated glass on glass door models.
- Pass-thru freezer designed to be rear-loaded from prep area and front accessed.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.