

Reach-In Glass Door Refrigerators



TA1R-2HG

Cabinets shown with various tray slide options

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
GLASS DOORS						
TA1R-1G	1	31	1/3	9.0	410	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TA2R-2G	2	56	1/2	11.4	710	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄
TA3R-3G	3	85	3/4	11.8	867	76 ¹ / ₂ x 34 ⁷ / ₈ x 78 ¹ / ₄
GLASS HALF DOORS						
TA1R-2HG	2	31	1/3	9.0	465	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TA2R-4HG	4	56	1/2	11.4	660	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄
COMBINATION HALF DOORS						
TA1R-1HG/1HS	2	31	1/3	9.0	465	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TA2R-2HG/2HS	4	56	1/2	10.0	640	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for door handle (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.



TA2R-2HG/2HS

FEATURES/BENEFITS

- **Shelving** - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. (field installation required).
- Oversized and balanced, **environmentally friendly, refrigeration system**, factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F**.
- **Fluorescent interior lighting**.
- Exterior - **300 series stainless steel front, sides, bottom and back** (the finest stainless available).

- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner** (solid doors).
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges**.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- **Energy efficient, "Low-E", thermal glass on glass door models**.
- Exterior mounted **digital electronic thermometer** features manual defogger.
- **Lifetime guaranteed recessed door handles** on solid doors.
- Door locks standard.

- Extruded, aluminum door frames on glass doors.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Refrigerator models feature **glass condensate pan** to prevent electrolysis.
- Hot gas condensate for energy efficiency.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.