

Reach-In Heated Cabinets



TA2H-2S

Model	Swing Doors	Cu. Ft.	Watts	Crated Weight	Cabinet Dimensions		
					L	D	H*
SOLID DOORS							
TA1H-1S ‡	1	31	2000	350	29	34 ³ / ₄	78 ¹ / ₄
TA2H-2S ‡	2	56	4000	565	51 ³ / ₈	34 ³ / ₄	78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

* Height does not include 6" for leg height or 5" for optional castors (castors available on single section models only).

‡ Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2H-2S requires hard wiring.

Pass-Thru Heated Cabinets



TA1H-1S

Model	Swing Doors	Cu. Ft.	Watts	Crated Weight	Cabinet Dimensions		
					L	D	H*
SOLID DOORS							
TA1HPT-1S-1S ‡	2	31	2000	400	29	37 ¹ / ₄	78 ¹ / ₄
TA2HPT-2S-2S ‡	4	56	4000	600	51 ³ / ₈	37 ¹ / ₄	78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

* Height does not include 6" for leg height or 5" for optional castors (castors available on single section models only).

‡ Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2HPT-2S-2S requires hard wiring.



TA2HPT-2S-2S

True Heated Cabinets are designed to hold warm baked or cooked food. Cabinets are not designed to heat ambient or cold product.

FEATURES/BENEFITS

- Powerfully provides **holding temperatures of 80°F to 180°F** throughout the cabinet for uniform, forced-air, heating.
- Low velocity fan(s) provided to assure even temperature throughout cabinet. A vent is located at the top of the cabinet for positive humidity control.
- **Heater - stainless steel for corrosion resistance.**
- **Shelving** - (3) heavy duty, chrome shelves per section with wall mounted pilasters (3) different interior kits available. (field installation required).
- **Exterior - 300 series stainless steel front, sides, bottom and back** (the finest stainless available).
- Anodized aluminum interior.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- Exterior mounted, **color coded, temperature monitor.**
- **Lifetime guaranteed recessed door handles standard.**
- Door locks standard.
- Doors equipped with lifetime guaranteed self-closing hinges with 90 degree stay open feature standard.
- Humidity control - 12" x 20" pan standard.
- **Manual humidity control** is a standard feature (turn counterclockwise to ventilate).
- Incandescent interior lighting.
- **6" legs standard** equipment. 4" diameter swivel castors available for single section models only.
- Pass-thru heated cabinet designed to be rear-loaded from prep area and front accessed.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)