


TA Series



Pass-Thru Refrigerators (front & rear solid doors)

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*
SOLID FRONT/SOLID REAR DOORS						
TA1RPT-1S-1S	2	31	1/2	10.4	410	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-2S-2S	4	56	3/4	15.5	710	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HS-1S	3	31	1/2	10.4	contact	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-4HS-2S	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

Pass-Thru Refrigerators (solid rear doors)

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
GLASS FRONT/SOLID REAR DOORS						
TA1RPT-1G-1S	2	31	1/2	10.4	contact	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2G-2S	4	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HG-1S	3	31	1/2	10.4	contact	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HG-2S	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-1HG/1HS-1S	3	31	1/2	10.4	contact	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2S	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for door handles (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

Pass-Thru Refrigerators (glass rear doors)

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
SOLID FRONT/GLASS REAR DOORS						
TA1RPT-1S-1G	2	31	1/2	10.4	contact	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2S-2G	4	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HS-1G	3	31	1/2	10.4	contact	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HS-2G	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT/GLASS REAR DOORS						
TA1RPT-1G-1G	2	31	1/2	10.4	contact	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2G-2G	4	56	3/4	15.5	factory	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HG-1G	3	31	1/2	10.4	contact	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-4HG-2G	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-1HG/1HS-1G	3	31	1/2	10.4	contact	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2G	6	56	3/4	15.5	factory	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for glass door handles, front or back.

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

FEATURES/BENEFITS

- **Shelving** - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. (field installation required).
- **Oversized and balanced, environmentally friendly, refrigeration system**, factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F**.
- Exterior - **300 series stainless steel front, sides, bottom and back** (the finest stainless available).
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner** (solid doors).
- The utility of the "TA" series pass-thru is in its ability to be a server station for cold dishes. Designed to become a central station, rear-loaded from the kitchen prep area to be front-accessed by servers.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- **Lifetime guaranteed recessed door handles**.
- Door locks standard.
- Exterior mounted **digital electronic thermometer** features manual defogger.
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges**.
- Incandescent interior lighting (solid doors); Fluorescent interior lighting (glass & combo doors).
- Extruded, aluminum door frames on glass doors.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Refrigerator models feature glass condensate pan to prevent electrolysis.
- Self-contained system.



TA1RPT-1S-1S



TA2RPT-2S-2S

True's TA Series 1 and 2 section pass-thru refrigerators can be built with any combination of half & full doors in both stainless steel and glass. Please contact your local True representative for nomenclature, pricing and lead times.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.