

## Roll-In Refrigerators

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*		
<b>SOLID DOORS</b>								
TA1RRI-1S	1	37	1/3	8.9	400	35	34 <sup>1</sup> / <sub>2</sub>	83 <sup>3</sup> / <sub>4</sub>
TA2RRI-2S	2	75	1/2	11.8	706	68	34 <sup>1</sup> / <sub>2</sub>	83 <sup>3</sup> / <sub>4</sub>
<b>SOLID DOORS 89" HIGH</b>								
TA1RRI89-1S	1	38	1/3	8.9	485	35	34 <sup>1</sup> / <sub>2</sub>	89
TA2RRI89-2S	2	80	1/2	11.8	786	68	34 <sup>1</sup> / <sub>2</sub>	89

All dimensions rounded up to the nearest 1/8".

\* Height does not include 1" for system mechanical components.

## Roll-Thru Refrigerators

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*		
<b>SOLID DOORS</b>								
TA1RRT-1S-1S	2	37	1/3	8.9	475	35	36 <sup>7</sup> / <sub>8</sub>	83 <sup>3</sup> / <sub>4</sub>
TA2RRT-2S-2S	4	75	1/2	9.5	781	68	36 <sup>7</sup> / <sub>8</sub>	83 <sup>3</sup> / <sub>4</sub>
<b>SOLID DOORS 89" HIGH</b>								
TA1RRT89-1S-1S	2	38	1/3	8.9	495	35	36 <sup>7</sup> / <sub>8</sub>	89
TA2RRT89-2S-2S	4	80	1/2	9.5	821	68	36 <sup>7</sup> / <sub>8</sub>	89

All dimensions rounded up to the nearest 1/8".

\* Height does not include 1" for system mechanical components.

*The new consultant choice for roll-in & roll-thru rack applications.*



TA1RRI89-1S



TA1RRI-1S

*Roll-thru models feature front and rear swing doors, each with a heavy duty stainless steel ramp for roll-thru service.*



TA2RRT-2S-2S

### FEATURES/BENEFITS

- Oversized and balanced, **environmentally friendly, refrigeration system**, factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F**.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. 89" high models accept roll-in/thru rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H. (supplied by others)
- Exterior - **300 series stainless steel doors, front, back & bottom. Stainless steel sides.**
- **Heavy gauge doors.**
- Interior - attractive, **NSF approved**, white aluminum sides and back. **300 series stainless floor and door liner.**
- Three rugged **cam-lift hinges** per door-lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- **Heavy gauge stainless steel ramp** standard for each door.
- Exterior mounted digital electronic thermometer features manual defogger.
- **Interior bumpers protect cabinet.**
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Incandescent interior lighting.
- **Energy saver switch.**
- **Lifetime guaranteed recessed door handles.**
- Door locks standard.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Glass condensate pan to prevent electrolysis.
- Hot gas condensate for energy efficiency.
- Self-contained system.
- Reversible wiper gaskets for positive seal.
- **Field reversible door swing.**

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.