



TA Series

Roll-In Heated Cabinets

Model	Swing Doors	Cu. Ft.	Watts	Crated Weight	Cabinet Dimensions L D H*
SOLID DOORS					
TA1HRI-1S ‡	1	37	2000	325	35 x 34 ¹ / ₂ x 83 ³ / ₄
TA2HRI-2S ‡	2	75	4000	615	68 x 34 ¹ / ₂ x 83 ³ / ₄
SOLID DOORS 89" HIGH					
TA1HRI89-1S ‡	1	38	2000	385	35 x 34 ¹ / ₂ x 89

All dimensions rounded up to the nearest 1/8".

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2HRI-2S requires hard wiring.

Roll-Thru Heated Cabinets

Model	Swing Doors	Cu. Ft.	Watts	Crated Weight	Cabinet Dimensions L D H*
SOLID DOORS					
TA1HRT-1S-1S ‡	2	37	2000	400	35 x 36 ⁷ / ₈ x 83 ³ / ₄
TA2HRT-2S-2S ‡	4	75	4000	706	68 x 36 ⁷ / ₈ x 83 ³ / ₄
SOLID DOORS 89" HIGH					
TA1HRT89-1S-1S ‡	2	38	2000	500	35 x 36 ⁷ / ₈ x 89

All dimensions rounded up to the nearest 1/8".

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2HRT-2S-2S requires hard wiring.



TA1HRT89-1S-1S



TA2HRT-2S-2S

True Heated Cabinets are designed to hold warm baked or cooked food. Cabinets are not designed to heat ambient or cold product.



TA1HRI-1S

FEATURES/BENEFITS

- Powerfully provides **holding temperatures of 80°F to 180°F** throughout the cabinet for uniform, forced-air, heating.
- Low velocity fan(s) provided to assure even temperature throughout cabinet. A vent is located at the top of the cabinet for positive humidity control.
- Heater - **stainless steel for corrosion resistance.**
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. TA1HRI89-1S and TA1HRT89-1S-1S accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H. (supplied by others).
- Exterior - **300 series stainless steel doors, front, back & bottom. Stainless steel sides.**
- Anodized aluminum interior.
- Humidity control - 12" x 20" pan standard.
- **Manual humidity control** is a standard feature (turn counterclockwise to ventilate).
- **Heavy gauge doors.**
- Three **ridged cam-lift hinges** per door-lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- Heavy gauge **stainless steel ramp** standard for each door.
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Exterior mounted, **color coded, temperature monitor.**
- **Lifetime guaranteed recessed door handles standard.**
- Door locks standard.
- Incandescent interior lighting.
- Self-contained system.
- **Reversible wiper gaskets** for positive seal.
- Interior bumpers protect cabinet.
- **Field reversible door swing.**
- Roll-thru heated cabinet designed to be rear-loaded from prep area and front accessed.