

Reach-In Solid Door Refrigerators

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*		
SOLID DOORS								
TR1R-1S	1	31	1/3	8.5	370	29	34 ³ / ₄	78 ¹ / ₄
TR2R-2S	2	56	1/2	10.0	650	51 ³ / ₈	34 ³ / ₄	78 ¹ / ₄
TR3R-3S	3	85	1/2	11.8	770	76 ¹ / ₂	34 ³ / ₄	78 ¹ / ₄
SOLID HALF DOORS								
TR1R-2HS	2	31	1/3	8.5	390	29	34 ³ / ₄	78 ¹ / ₄
TR2R-4HS	4	56	1/2	10.0	650	51 ³ / ₈	34 ³ / ₄	78 ¹ / ₄
TR3R-6HS	6	85	1/2	11.8	770	76 ¹ / ₂	34 ³ / ₄	78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.

Deep reach-in's provide greater depth to accept full sized pans.



TR1R-2HS



TR3R-3S



TR2R-2S

FEATURES/BENEFITS

- **Shelving** - (1) interior kit option included per full section at no charge. (4) different interior kits available.
- **Pilasters and tray slides/shelving are factory installed at no charge.**
- **Oversized and balanced, environmentally friendly, refrigeration system,** factory sealed and pre-lubricated for long life.
- Food safe refrigerators **hold 33°F to 38°F.**
- Exterior - **300 series stainless steel front, sides, bottom and back** (the finest stainless available).
- Interior - **300 series stainless steel walls, back, floor & door liner.**
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- **Lifetime guaranteed recessed door handles.**
- Exterior mounted **digital electronic thermometer** features manual defogger.
- Positive seal self-closing doors with 90 degree stay open feature. **Lifetime guaranteed door hinges.**
- Door locks standard.
- Incandescent interior lighting.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Refrigerator models feature glass condensate pan to prevent electrolysis.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.