



300 Series Stainless Steel, Glass & Solid Half Door Freezers



TS-23FG

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H*
GLASS FULL DOORS									
TS-23FG	1 gls	23	3	3/4	13.0	430	27	29 ³ / ₄	78 ³ / ₈
TS-49FG ‡	2 gls	49	6	1 ¹ / ₂	12.3	605	54 ¹ / ₈	29 ³ / ₄	78 ³ / ₈
NEW TS-72FG ‡	3 gls	72	9	1 ¹ / ₂	14.1	N/A	78 ¹ / ₈	29 ³ / ₄	79 ¹ / ₈
SOLID HALF DOORS									
TS-23F-2	2 s/s	23	3	1/2	10.4	330	27	29 ¹ / ₂	78 ³ / ₈
TS-49F-4	4 s/s	49	9	3/4	13.2	560	54 ¹ / ₈	29 ¹ / ₂	78 ³ / ₈

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for door handle (glass door models only).

* Height does not include 5" for castors or 6" for optional legs.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



TS-49F-4



TS-72FG

FEATURES/BENEFITS

- **Oversized and balanced refrigeration system**, factory sealed and pre-lubricated for long life.
- **Environmentally friendly (R404A), refrigerant.**
- **-10°F temperature** (air off evaporator coil, -20°F) - holds frozen food and ice cream.
- True's "TS" series is the choice for the exclusive 300 series stainless steel commercial application.
- **300 series stainless steel interior and exterior** front & sides, with matching aluminum back.
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- Minimum wattage heater in cabinet frame and door.
- **Energy efficient, triple pane, thermal insulated glass on glass door models.**
- Standard backguard improves airflow.
- **Solar, digital thermometer** standard for easy visibility.
- Positive seal self-closing doors with factory tested (over 1,000,000 times) **lifetime guaranteed door hinges and torsion type closure system.**
- **Lifetime guaranteed recessed door handles on solid doors.**
- Extruded, aluminum door frames on glass doors.
- Incandescent interior lighting on solid door models.
- Fluorescent interior lighting; integrated door light (IDL) standard on glass door models.
- Adjustable, **heavy duty, PVC coated wire shelves.**
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Door locks standard.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Self-contained system.
- Bottom mount compressor.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.