



TS Series

300 Series Stainless Steel Refrigerators

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*		
SOLID DOORS									
TS-23	1 s/s	23	3	1/3	7.6	295	27	x 29 ¹ / ₂	x 78 ³ / ₈
TS-35	2 s/s	35	6	1/2	9.2	395	39 ¹ / ₂	x 29 ¹ / ₂	x 78 ³ / ₈
TS-49	2 s/s	49	6	1/2	9.5	465	54 ¹ / ₈	x 29 ¹ / ₂	x 78 ³ / ₈
TS-72	3 s/s	72	9	1/2	11.8	635	78 ¹ / ₈	x 29 ¹ / ₂	x 79 ¹ / ₈
GLASS DOORS									
TS-23G	1 g/s	23	3	1/3	7.9	305	27	x 29 ³ / ₄	x 78 ³ / ₈
TS-49G	2 g/s	49	6	1/2	10.0	490	54 ¹ / ₈	x 29 ³ / ₄	x 78 ³ / ₈
TS-72G	3 g/s	72	9	1/2	12.9	675	78 ¹ / ₈	x 29 ³ / ₄	x 79 ¹ / ₈

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1³/₈" for door handle (glass door models only).

* Height does not include 5" for castors or 6" for optional legs.

For customers who demand the finest in design, engineering, and materials - True's "TS" series - Stainless Interior/Exterior.



TS-23



TS-72G



TS-49

FEATURES/BENEFITS

- **Oversized and balanced, environmentally friendly (134A), refrigeration system**, factory sealed and pre-lubricated for long life - holds **33°F to 38°F**.
- True's "TS" series is the choice for the exclusive 300 series stainless steel commercial application. Designed with enduring quality that protects your long-term investment, and oversized refrigeration that guarantees superior food preservation.
- **300 series stainless steel interior and exterior** front & sides, with matching aluminum back.
- **Energy efficient, "Low-E", thermal glass on glass door models.**
- **Solar, digital thermometer** standard for easy visibility.
- Incandescent interior lighting on solid door models.
- Fluorescent interior lighting; **integrated door light (IDL)** standard on glass & combination door models.
- Adjustable, **heavy duty, PVC coated wire shelves.**
- Positive seal self-closing doors with factory tested (over 1,000,000 times) **lifetime guaranteed door hinges and torsion type closure system.**
- **Lifetime guaranteed recessed door handles** on solid doors.
- Extruded, aluminum door frames on glass doors.
- Foamed-in-place polyurethane **high density cell insulation** (CFC free).
- Door locks standard.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Bottom mount compressor.
- Self-contained system.
- TS-23, -49, -72 available with alternative hinge orientations (no charge).

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.