



Undercounters

Undercounter Refrigerators

Model	Doors/ Drawers	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*		
TUC-27	1/0	6.5	2	1/6	3.9	190	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-36	2/0	8.5	4	1/6	4.7	225	36 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48	2/0	12.0	4	1/5	5.0	270	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-60	2/0	15.5	4	1/5	5.1	320	60 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-72	3/0	19.0	6	1/3	8.5	390	72 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
GLASS DOORS									
TUC-27G	1/0	6.5	2	1/6	3.9	210	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48G	2/0	12.0	4	1/5	5.0	290	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-60G	2/0	15.5	4	1/5	5.1	360	60 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
DRAWERED									
TUC-27D-2	0/2	6.5	N/A	1/6	3.9	210	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48D-2	1/2	12.0	2	1/5	5.0	310	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48D-4	0/4	12.0	N/A	1/5	5.0	310	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-60D-2	1/2	15.5	2	1/5	5.1	380	60 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-60D-4	0/4	15.5	N/A	1/5	5.1	380	60 ³ / ₈	30 ¹ / ₈	29 ³ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1" for rear bumpers.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.



TUC-27



TUC-48F-D-4



TUC-60G

Undercounter Freezers

Model	Doors/ Drawers	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*		
TUC-27F	1/0	6.5	2	1/3	8.3	195	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48F	2/0	12.0	4	1/2	10.9	300	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-60F	2/0	15.5	4	1/2	10.9	355	60 ³ / ₈	30 ¹ / ₈	29 ³ / ₄
GLASS DOORS									
TUC-27FG	1/0	6.5	2	1/2	8.6	230	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
DRAWERED									
TUC-27F-D-2	0/2	6.5	N/A	1/3	7.4	215	27 ⁵ / ₈	30 ¹ / ₈	29 ³ / ₄
TUC-48F-D-4	0/4	12.0	N/A	1/2	10.9	355	48 ³ / ₈	30 ¹ / ₈	29 ³ / ₄

All dimensions rounded up to the nearest 1/8".

† Depth does not include 1" for rear bumpers.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.

Low Profile &
ADA Compliant Castor
Packages Available

TUC MODELS
Heavy, 16 Gauge Tops
All TUC-27 models
All TUC-36 models
All TUC-48 models
All TUC-60 models
All TUC-72 models

FEATURES/BENEFITS

- Oversized, **environmentally friendly refrigeration system** (refrigerators: 134A / freezers: R404A).
- Refrigerator **holds 33°F to 38°F** temperature; freezer **holds -10°F**.
- Automatic defrost system on freezer models time-initiated, time-terminated.
- 360° circular airflow for uniform product cooling.
- All stainless steel front, top and sides.**
- Interior - attractive, **NSF approved**, white aluminum sides and top, coved corners and **300 series stainless steel floor**.
- Aluminum finished back.**
- Adjustable, **heavy duty, PVC coated wire shelves** (not available in drawered models).
- Easily slides under counters, maximizes space for refrigerated food storage in fast food line-up.

- Front breathing.
- Recessed handles (excludes glass door models).
- Swing doors are self-closing with 90 degree stay open feature (excludes center door on TUC-72's).
- Doors swing within cabinet dimensions.
- Self-contained system.
- Foamed-in-place **high density polyurethane insulation** (CFC free).
- 5" diameter castors** standard equipment (legs available).
- Work surface 36" high.
- Low profile models (31⁷/₈" work surface height) upcharge applies or ADA compliant with 34" work surface height available; no charge. (models -27, -36, -48, -60, -72).
- Heavy, 16 gauge tops available - upcharge applies.

Glass Door Models

- Energy efficient, "Low-E", thermal glass doors on refrigerator models** (triple pane thermal insulated glass on freezer models).
- Extruded, aluminum door frames on glass doors.
- Fluorescent interior lighting.

Drawered Models

- Accommodates one 12"L x 20"W x 6"D full size pan or two 1/2 pans or three 1/3 pans per drawer. (48" models accommodate one 12"L x 18"W x 6"D food storage box or one 1/3 size and one 1/2 size pan per drawer; not included).
- Door/drawer combination models require customer to designate door/drawer orientation.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.